

SAFETY DATA SHEET

SUPERCLEAN

Page 1

Issued: 21/12/2004

Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: SUPERCLEAN

Company name: Advanced Engineering Limited

Guardian House

Stroudley Road

Basingstoke

Hampshire

RG24 8NL

United Kingdom

Tel: +44(0) 1256 46 03 00

Fax: +44(0) 1256 46 22 66

Emergency tel: +44(0) 1256 46 03 00

2. COMPOSITION / INFORMATION ON INGREDIENTS

- Hazardous ingredients:** SODIUM HYDROXIDE 10.000%
EINECS: 215-185-5 CAS: 1310-73-2
[C] R35
- POTASSIUM HYDROXIDE 20.000%
EINECS: 215-181-3 CAS: 1310-58-3
[Xn] R22; [C] R35

3. HAZARDS IDENTIFICATION

Main hazards: Causes severe burns.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If

[cont...]

SAFETY DATA SHEET

SUPERCLEAN

unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

Exposure hazards: Corrosive. In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: SODIUM HYDROXIDE
STEL (15 min exposure limit): 2 mg/m³ (OES)

- POTASSIUM HYDROXIDE
STEL (15 min exposure limit): 2 mg/m³ (OES)

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Brown

Odour: Characteristic odour

Evaporation rate: Slow

Solubility in water: Soluble

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: SODIUM HYDROXIDE

IPR MUS LD50 40 mg/kg

ORL RBT LDLO 500 mg/kg

• POTASSIUM HYDROXIDE

ORL RAT LD50 273 mg/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

Persistence and degradability: Biodegradable.

Bioaccumulative potential: No bioaccumulation potential.

Other adverse effects: Negligible ecotoxicity.

13. DISPOSAL CONSIDERATIONS

Disposal of packaging: Clean with water. Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: 1719

ADR Class: 8

Packing group: II

Classification code: C5

Shipping name: CAUSTIC ALKALI LIQUID, N.O.S.

SAFETY DATA SHEET

SUPERCLEAN

Labelling: 8

Hazard ID no: 80



IMDG / IMO

UN no: 1719	Class: 8
Packing group: II	EmS: F-A,S-B
Marine pollutant: .	Labelling: 8

IATA / ICAO

UN no: 1719	Class: 8
Packing group: II	Packing instructions: 809(P&CA); 813(CAO)
Labelling: 8	

15. REGULATORY INFORMATION

Hazard symbols: Corrosive.



Risk phrases: R35: Causes severe burns.

Safety phrases: S23: Do not breathe spray.

S51: Use only in well-ventilated areas.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.2: R35: Causes severe burns.

R22: Harmful if swallowed.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.